U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

Form Approved OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

MAY 28 1982

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

	SECT	ION I	. 0	DPM	5	541
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.					
Turco Products, Inc.			: (213). 634 - 3	300	
ADDRESS (Number, Street, City, State, and ZIP Coo 24600 South Main Stree	t, Carso	n, Califor	cnia 90	749		
CHEMICAL NAME AND SYNONYMS		TRA	DE NAME AND	SYNONYMS	3	0
CHEMICAL FAMILY		FORMULA		" "		
SECTIO HAZARDOUS MIXT	ON II - HAZAR	DOUS INGREDIEN	TS R GASES			
		C.A.S. NUMBER	DOT SPILL CAT.	EPA WASTE NUMBER	%	TLV UNITS
Phosphoric Acid		7664- 38-2		D002	55	1Mg/M ³
Butyl Cellosolve		111-76-2	Un- listed	Un- listed	15	550 PPM SKIN
Other components not defi	ned as ha	azardous b	ov the U	.S. Depi		f Labor.
The moral are, and the last						
Carcinogens	4	f':. · · · · · · · · ·	A 7 .	NONE		
SECT	ΓΙΟΝ ΙΙΙ - Ρ	HYSICAL DA	TA	o padaranan a maka paka ka 		
BOILING POINT (°F.) Approx.	212°F	SPECIFIC GRAVITY (H2O=1)			1.34	
VAPOR PRESSURE (mm Hg.) Approx.	25mm	PERCENT, VOLATILE BY VOLUME (%) 40			40	
VAPOR DENSITY (AIR=1) More than	1	EVAPORATION RATE (Bu. Ac. =1) More than 1				
SOLUBILITY IN WATER	Complete					
APPEARANCE AND ODOR Clear color						
SECTION IV - F	FIRE AND E	XPLOSION H	AZARD D	ATA	· .	
FLASH POINT (Method used) None		FLAMMABLE	LIMITS	Le		l Uni mmable
EXTINGUISHING MEDIA NA				INOIL		mmad te
SPECIAL FIRE FIGHTING PROCEDURES	ermal Dec	compositio	n will r	roduce	tov	ic
Oxides of phosphorous. We	ar cae n	nacke''	vv	Minney	LUA	<u> </u>
UNUSUAL FIRE AND EXPLOSION HAZARDS	-ur <u>- 600 11</u>	<u> </u>			,	****
						·
			-	والمراوية		

Proglamond.

Carrie MEHA 20

				<u></u>			
	SI	ECTION \	/ - HEA	L TH HAZARD	DATA	·	
THRESHOLD LIMIT		See Se	ction	II			
EFFECTS OF OVER Skin: Mo	exposure derate to se	evere i	rritat	ion. Eyes	: Severe	irritati	on, pos-
sible co	rneaí damage	. Tno	estion	· Severe i	rritation	of Dico	stine to
EMERGENCY AND Skin: Wa	FIRST AID PROCEDU sh well with	RES 1 Soap	and wa	ter. If ir	ritation m	persists	. obtain
medical at	tention. Ey	es: Fl	ush wi	th water f	or at leas	st 15 mi	nutes.
	ical attenti otain Medica						
or milities o	, .			EACTIVITY DA			
STABILITY	UNSTABLE			S TO AVOID			
, , , , , , , , , , , , , , , , , , ,	STABLE	77			`(
INCOMPATABILITY	(Materials to avoid)	X	•			711111111111111111111111111111111111111	
HAZARDOUS DEC	MPOSITION PRODUC	TS		erials .			
Thermal De	Composition MAY OCCUP	will p	roduce	toxic oxid	des of pho	sphorou	S
HAZARDOUS POLYMERIZATION	WILL NOT O						
	WILL NOT C		X	1	,		
	SECT	ION VII	- SPILL	OR LEAK PRO	CEDURES		
STEPS TO BE TAK	EN IN CASE MATERIA	AL IS RELE	ASED OR S	Avoid	contact w	vith ski	n and
clothing.	Neutralize	acidi	ty and	flush to s			
a le responsable de	• 6		i			· Contraction	
WASTE DISPOSAL	Neutra Neutra	lize a	cidity	. Treat to	remove ph	osphates	if
required 1	y Local or						
	SECTION	VIII - SP	FCIAL P	ROTECTION IN	VEORMATION	Ų	· · · · · · · · · · · · · · · · · · ·
RESPIRATORY PRO	TECTION (Specify ty						
VENTILATION	LOCAL EXHAUST	-	·		SPECIAL		
	MECHANICAL (Gen	ieral) X			OTHER		
PROTECTIVE GLOV				EYE PROTECTION	N		
OTHER PROTECTIV	Rubber E EQUIPMENT			<u> </u>	Splash g	dggles_	
		······································					'
	SE	CTION I	X - SPE	CIAL PRECAUT	TIONS		
PRECAUTIONS TO	BE TAKEN IN HANDL	ING AND S	TORING	cansport ar	nd store i	n closed	l con-
tainers at	temperatur	es betv	veen 30	0°F and 120)°F.		
OTHER PRECAUTIO	NIC			in,eyes and		granitani n	
	,			1		₩-	

PAGE (2)

GPO 934-110

Form OSHA-20